Application No.: Not Yet Assigned

14

AMENDMENTS TO THE CLAIMS

- 1. (Canceled)
- 2. (Canceled)
- 3. (Canceled)
- 4. (Canceled)
- 5. (Canceled)
- 6. (Canceled)
- 7. (Canceled)
- 8. (Canceled)
- 9. (Canceled)
- 10. (Canceled)
- 11. (Canceled)
- 12. (Canceled)
- 13. (Canceled)
- 14. (Canceled)
- 15. (Canceled)
- 16. (Canceled)
- 17. (Canceled)

- 18. (Canceled)
- 19. (Canceled)
- 20. (Canceled)
- 21. (Canceled)
- 22. (Canceled)
- 23. (Canceled)
- 24. (Canceled)
- 25. (Canceled)
- 26. (Canceled)
- 27. (Canceled)
- 28. (Canceled)
- 29. (Canceled)
- 30. (Canceled)
- 31. (Canceled)
- 32. (Canceled)
- 33. (Canceled)
- 34. (Canceled)
- 35. (Canceled)
- 36. (Canceled)

16

Application No.: Not Yet Assigned

- 37. (Canceled)
- 38. (Canceled)
- 39. (Canceled)
- 40. (Canceled)
- 41. (Canceled)
- 42. (Canceled)
- 43. (Canceled)
- 44. (Canceled)
- 45. (Canceled)
- 46. (Canceled)
- 47. (Canceled)
- 48. (Canceled)
- 49. (Canceled)
- 50. (Canceled)
- 51. (Canceled)
- 52. (Canceled)
- 53. (Canceled)
- 54. (Canceled)
- 55. (Canceled)

17

- 56. (Canceled)
- 57. (Canceled)
- 58. (Canceled)
- 59. (Canceled)
- 60. (Canceled)
- 61. (Original) A method for controlling an ultrasonic surgical handpiece using a switch located on a housing of the handpiece, comprising the steps of:

monitoring pressure applied to the housing using the switch; activating the handpiece at a first power level if the monitored pressure reaches a high threshold; and

deactivating the handpiece if the monitored pressure reaches a low threshold.

- 62. (Original) The method of claim 61 further comprising the step of operating the handpiece at a power level selected from a plurality of power levels if the monitored pressure reaches a specific threshold of a respective plurality of thresholds corresponding to the plurality of power levels.
- 63. (Original) The method of claim 61 wherein the pressure is monitored by a sensor located inside the housing of the handpiece selected from a group consisting of an electro-mechanical switch, a force-sensitive resistor, force sensitive capacitor, strain gauge, magnet, ferromagnet, piezo film and piezo ceramic.
- 64. (Original) The method of claim 61 wherein the switch is generally aligned with the blade as the blade is rotated.

Docket No.: 02640/100G819-US2

- 65. (Original) The method of claim 61 wherein the switch provides its switching functionality according to a lagging effect as the monitored pressured is changed.
- 66. (Canceled)
- 67. (Canceled)
- 68. (Canceled)